

Residual stresses in multi-pass cold drawn high-strength steel wires

Andrea Panteghini¹, Francesco Genna², Alberto Franchi³

¹ *Department of Civil Engineering, University of Brescia, Italy*

E-mail: andrea.panteghini@ing.unibs.it

² *Department of Civil Engineering, University of Brescia, Italy*

E-mail: francesco.genna@ing.unibs.it

³ *Department of Structural Engineering, Politecnico di Milano, Italy*

E-mail: alberto.franchi@polimi.it

Keywords: wire drawing, finite element method, cold forming

SUMMARY. Cold drawing is employed to fabricate wire and rods, which are mainly used as structural reinforcements in prestressed concrete structures, in tyres, but also as cables in deepes mines shafts and off-shore petroleum production. As a consequence of the drawing process, a residual stress profile is developed [Atienza et al., 2005b] [Atienza et al., 2005a]. The drawing process is complex, and there are many parameters that determine the deformation and therefore the final state of residual stresses [Overstam, 2006]. Some studies [Elices et al., 2004] [Atienza and Elices, 2003] have demonstrated the influence of residual stresses on the stress relaxation losses and on the ductility in steel wires. In prestressed concrete structures, stress relaxation losses in steel cables are very important, and design codes place both limits on the initial prestress load and recommendations for keeping these losses within safe margins. Wire manufacturers know the harmful effects of residual stresses, and try to reduce their influence by thermo-mechanical treatments [6] after drawing. These treatments are often empirical, because of the difficulty to model these processes. It is desirable for the industry to find an efficient way to study the influence of the drawing process and heat treatment variables on residual stresses. Hence, it would be advantageous to predict the distribution of residual stresses generated by cold-drawing and by the subsequent heat treatment. This paper presents a study on the multi-pass drawing of a wire of high-strength steel by means of the finite element method (FEM), and on the effects of the thermo-mechanical treatments on the residual stresses in the wire. A FEM model of the drawing process and of the heat treatment is presented. The results show that the post-drawing treatment is very successful in reducing the residual stresses produced by the drawing, suggesting that the FEM method could be used to design and optimize this specific industrial process.

References

- [Atienza and Elices, 2003] Atienza, J. and Elices, M. (2003). Influence of residual stresses in stress tensile test of cold drawn wires. *Materials and Structures*, 36(10):548–552.
- [Atienza et al., 2005a] Atienza, J., Martinez-Perez, M., Ruiz-Hervias, J., Mompean, F., Garcia-Hernandez, M., and Elices, M. (2005a). Residual stresses in cold drawn ferritic rods. *Scripta Materialia*, 52:305–309.
- [Atienza et al., 2005b] Atienza, J., Ruiz-Hervias, J., Martinez-Perez, M., Mompean, F., Garcia-Hernandez, M., and Elices, M. (2005b). Residual stresses in cold drawn pearlitic rods. *Scripta Materialia*, 52:1223–1228.

- [Elices et al., 2004] Elices, M., Ruiz, J., and Atienza, J. (2004). Influence of residual stresses in stress relaxation of cold drawn wires. *Materials and Structures*, 37(6):301–304.
- [Overstam, 2006] Overstam, H. (2006). The influence of bearing geometry on residual stress state in cold drawn wire, analyzed by the fem. *Journal of Material Processing Technology*, 171:446–450.